

## 热轧六角钢、八角钢（GB 705-89）

### 1、尺寸与理论重量

对边距离 S(mm)	截面面积(cm <sup>2</sup> )		理论重量(kg/m)		对边距离 S(mm)	截面面积(cm <sup>2</sup> )		理论重量(kg/m)	
	六角钢	八角钢	六角钢	八角钢		六角钢	八角钢	六角钢	八角钢
8	0.5543	—	0.435	—					
9	0.7015	—	0.551	—					
10	0.866	—	0.680	—	32	8.868	8.479	6.96	6.66
11	1.048	—	0.823	—	34	10.011	9.572	7.86	7.51
12	1.247	—	0.979	—	36	11.223	10.731	8.81	8.42
13	1.464	—	1.15	—	38	12.505	11.956	9.82	9.39
14	1.697	—	1.33	—	40	13.86	13.25	10.88	10.40
15	1.949	—	1.53	—	42	15.28	—	11.99	—
16	2.217	2.120	1.74	1.66	45	17.54	—	13.77	—
17	2.503	—	1.96	—	48	19.95	—	15.66	—
18	2.806	2.683	2.20	2.16	50	21.65	—	17.00	—
19	3.126	—	2.45	—					
20	3.464	3.312	2.72	2.60					
21	3.819	—	3.00	—	53	24.33	—	19.10	—
22	4.192	4.008	3.29	3.15	56	27.16	—	21.32	—
23	4.581	—	3.60	—	58	29.13	—	22.87	—
24	4.988	—	3.92	—	60	31.18	—	24.50	—
25	5.413	5.175	4.25	4.06	63	34.37	—	26.98	—
26	5.854	—	4.60	—	65	36.59	—	28.72	—
27	6.314	—	4.96	—	68	40.44	—	31.43	—
28	6.790	6.492	5.33	5.10	70	42.30	—	33.30	—
30	7.794	7.452	6.12	5.85					

注：供应长度：普通钢 3m-8m，优质钢 2m-6m。



↑  
访问我们的官方网站了解更多内容

← 扫描二维码关注